

Data Sheet

2462 Duragauge® Pressure Gauge with PLUS!™ Performance Option

FEATURES

- Solid front safety case with pressure relief back
- Wide selection of bourdon tube materials, pressure connections and pressure ranges
- **PLUS!™** Performance dampens vibration, shock and pulsation effects

TYPICAL USES

- Refineries
- Chemical and petrochemical plants
- Offshore oil rigs
- Water and wastewater pressure control
- Pulp and water
- Mining and metals
- Equipment skids
- Specialized OEM equipment



2462
6" dial size



SPECIFICATIONS

Accuracy:	±0.5% of span (ASME B40.100, Grade 2A)
Dial Size:	6"
Range:	Vacuum to 30,000 psi
Process Connection Location:	Lower, back
Process Connection Size:	¼ NPT Male, ½ NPT Male, ⅜ -18 UNF-2B (high pressure connection)
Case Style:	Solid front with pressure relief back
Movement:	Rotary, adjustable, 400 SS, Teflon™ coated
Window Material:	Glass (STD.), safety glass, acrylic (OPT.)
Dial:	Aluminum, white background, black pressure scale
Pointer:	Micrometer adjustable, aluminum
Weather Protection:	Dry case: Case not sealed, recommended for weather protected environment only
Dampening Options:	PLUS!™ , Throttle screw, dampeners, capillary, diaphragm seals and snubbers
Mounting:	Stem, surface, flush
Approvals:	CRN, CE/UKCA

WETTED COMPONENTS

Bourdon Tube	Process Connection Materials	Joints
316L Stainless steel	316L Stainless steel	Welded
316L Stainless steel	Steel	Welded
K-Monel® 500 Tube	Monel® 400	Welded
C510 Phos. Bronze	Brass	Silver brazed

KEY BENEFITS

- Good value when 6" dial is required
- Corrosion resistance
- Uncompromised standards and material integrity

NON-WETTED COMPONENTS

Case	Ring	Pressure Relief Back
Polypropylene	Polypropylene	Polypropylene

MIN/MAX TEMPERATURE LIMITS

Version	Ambient	Process	Storage
Dry	-20 °F to 200 °F (-29 °C to 93 °C)	-20 °F to 250 °F (-29 °C to 121 °C)	-40 °F to 250 °F (-40 °C to 121 °C)
PLUS!™	-40 °F to 150 °F (-40 °C to 66 °C)	-40 °F to 200 °F (-40 °C to 93 °C)	-40 °F to 150 °F (-40 °C to 66 °C)

Note: Other than discoloration of the dial and hardening of the gasketing that may occur as ambient or process temperatures exceeds 150 °F, non-liquid-filled gauges with standard glass windows, can withstand continuous operating temperatures up to 250 °F (121 °C). Liquid-filled gauges can withstand 200 °F (93 °C) but glycerin fill and acrylic window will tend to yellow. Accuracy at temperatures above or below the reference ambient temperature of 68 °F (20 °C) will be affected by approximately 0.4% per 25 °F. Gauges with welded joints will withstand 750 °F (400 °C), 450 °F (232 °C) with silver brazed joints for short times without rupture, although other parts of the gauge will be destroyed and calibration will be lost. For continuous use and for process or ambient temperatures above 250 °F (121 °C), a diaphragm seal or capillary or siphon is recommended.

Data Sheet

2462 Duragauge® Pressure Gauge with PLUS!™ Performance Option

ORDERING CODE	Example:	602462	S	S	04	L	XLL	15#
Dial Size/Model Code								
602462 - 6" polypropylene case, solid front		602462						
System (tube and process connection)								
A - Bronze tube, brass process connection, max. pressure connection 1,000 psi								
P - K-Monel® 500 tube, Monel® 400 process connection, max. pressure 30,000 psi								
R - 316L Stainless steel tube, steel process connection, max. pressure 20,000 psi								
S - 316 Stainless steel tube, 316L Stainless steel process connection, max. pressure 20,000 psi			S					
Case Design								
S - Solid front case, dry				S				
Process Connection Sizes								
02 - ¼ NPT Male, N/A for ranges over 20,000 psi								
04 - ½ NPT Male, N/A for ranges over 20,000 psi					04			
09 - ¾ 18 UNF-2B, Aminco® high pressure fitting, standard for pressures over 20,000 psi								
Process Connection Location								
L - Lower						L		
B - Back								
D - Side (3 o'clock)								
E - Side connection (9 o'clock)								
T - Top connection								
Options (If choosing an option(s) must include a "X") (See Table 1 on page 3 for more options)								X_
Dampening								
LL - PLUS!™ Performance							LL	
NZ - PLUS!™ Performance silicone free								
6B - Cleaned for gaseous oxygen service								
NH - Stainless steel tag wired to case								
5G - Attach one accessory to gauge. Applicable to PL02 pressure limiting valve, V01, V02, V03 valves, 1098, 1100, 1198, 2198 siphons, 7001, 7004 needle valves, 1115 capillary, 1106 pulsation dampner, 1112, PD02 pressure snubbers, MDV swivel adapter, 2265 electric warning contact								
Range (coding examples only, see range table on page 3 for all standard ranges)								
Single Scales								
15# - 15 psi								15#
1BR - 1 bar								
1KG - 1 kilograms per sq. cm								
100KP - 100 kilopascal								
Dual Scales								
15#/BR - 15 psi inner scale, 1 bar outer scale								
1BR/# - 1 bar inner scale, 15 psi outer scale								

When selecting a diaphragm seal or isolation ring, refer to the [Min/Max Guide](#) for compatibility with this gauge or scan the QR code to the right.



Data Sheet

2462 Duragauge® Pressure Gauge with PLUS!™ Performance Option

TABLE 1 (Ordering Codes Continued)

CODE	OPTION
AB	Gauges calibrated to compensate for absolute pressure
DA	Dial marking (text marking on the dial)
EP	Maximum pointer (adjustable, N/A with liquid filled or hermetically sealed cases)
HY	Hydrostatic/pneumatic testing (system pressurized to 150% of rated system pressure for 5 minutes. Overload stop STD.)
NG	Non-glare glass
PD	Acrylic window
SG	Safety glass
SH	Red set hand, stationary
OS	Overload stop
TS	Throttle screw (STD. with PLUS!™ Performance)
VS	Underload stop
C4	Traceable calibration certificate

STANDARD PRESSURE RANGES					
	psi	bar	kPa	mPa	kg/cm²
Vacuum	30IMV	N1BR	N100KP	N1MP	N1KG
	-	N1/0.6BR	N100/60KP	0.1/0.06MP	N1/0.6KG
Compound	V/15#	-	-	-	-
	-	N1/1.5BR	N100/150KP	N0.1/0.15MP	N1/1.5KG
	V/30#	-	-	-	-
	-	N1/3BR	N100/300KP	N0.1/0.3MP	N1/3KG
	V/60#	-	-	-	-
	-	N1/5BR	N100/500KP	N0.1/.5MP	N1/5KG
	V/100#	-	-	-	-
	-	N1/9BR	N100/900KP	N0.1/.9MP	N1/9KG
	15#	1BR	100KP	0.1MP	1KG
	20#	-	-	-	-
	-	1.6BR	160KP	0.16MP	1.6KG
	30#	-	-	-	-
	-	2.5BR	250KP	0.25MP	2.5KG
	60#	4BR	400KP	0.4MP	4KG
	-	6BR	600KP	0.6MP	6KG
	Positive Pressure	100#	-	-	-
120#		-	-	-	-
-		10BR	1000KP	1MP	10KG
160#		-	-	-	-
200#		-	-	-	-
-		16BR	1600KP	1.6MP	16KG
300#		-	-	-	-
-		25BR	2500KP	2.5MP	25KG
400#		-	-	-	-
500#		-	-	-	-
600#		40BR	4000KP	4MP	40KG
800#		-	-	-	-
-		60BR	6000KP	6MP	60KG
1000#		-	-	-	-
1500#		100BR	10000KP	10MP	100KG
2000#		-	-	-	-
-		160BR	16000KP	16MP	160KG
3000#		-	-	-	-
-		250BR	25000KP	25MP	250KG
4000#		-	-	-	-
5000#	-	-	-	-	
6000#	400BR	40000KP	40MP	400KG	
8000#	-	-	-	-	
-	600BR	60000KP	60MP	600KG	
10000#	-	-	-	-	
15000#	1000BR	100000KP	100MP	1000KG	
20000#	-	-	-	-	
-	1600BR	-	160MP	1600KG	
30000#	-	-	-	-	
-	2500BR	-	250MP	2500KG	
50000#	-	-	-	-	
-	4000BR	-	400MP	4000KG	
80000#	-	-	-	-	
-	6000BR	-	600MP	6000KG	
100000#	-	-	-	-	

Data Sheet

2462 Duragauge® Pressure Gauge with PLUS!™ Performance Option

DIMENSIONS in [] are millimeters

For reference only, consult Ashcroft for specific dimensional drawings

Dial Size Inches	A	B	C	D	E	F	G	H	H ₁	J	KK	LL		M	S	T	Weight (lbs)
												Min.	Max.				
6	6 ⁵ / ₁₆ [163]	2 ⁷ / ₁₆ [62]	4 ³ / ₄ [120]	7/ ₈ [22]	5 ³ / ₈ [137]	1 ⁵ / ₈ [42]	3 ¹⁵ / ₁₆ [100]	4 ⁹ / ₁₆ [116]	4 ⁴ / ₃₂ [109]	5/ ₆₄ [2]	2 ¹¹ / ₁₆ [69]	1/ ₁₆ [2]	1/ ₂ [13]	6 [152]	1 ¹ / ₁₆ [17]	5/ ₁₆ [16]	2.0 (Dry)

